All Rubber Pads

Submittal Information >>>

Part No Document No. Date Revision MP-2/MP-3/MP-4/MP-6/MP-18 SPECMP-2 2021-10-13 02

General Properties >>

Material:RubberColor:BlackMaximum bearing capacity:50 lbs. per square inch

Application 渊

Designed for air conditioners, compressors, cooling towers, presses, machines or anywhere vibration control is needed.

- Vibration Isolation
- Noise Absorbing
- Anti-slip

Specification >>>

Item No.	Specifications	U/M	Std. Pkg.
MP-2	2" x 2" x 3/8"	EA	18
MP-3	3" x 3" x 3/8"	EA	24
MP-4	4" x 4" x 3/8"	EA	24
MP-6	6" x 6" x 3/8"	EA	24
MP-18	18" x 18" x 3/8"	EA	6

Features 🅦

- Made from high quality elastic materials, compounded for excellent resistance to aging, compression set & oil.
- Solid ribbed design add the isolation and positive grip.
- Have excellent vibration-reducing effect.
- The rubber pads are corrugated on both sides to reduce vibration and noise.
- Recommended maximum loading capacity: 50 lbs per square in.
- **Note:** This pad is made of industrial-grade rubber with excellent performance and will emit rubber odor. If you plan to use indoors, we recommend placing these mats in an open area for at least a week. Washing with soap will also partially reduce the odor.



Manufacturing Factory: 116# HaiXi S.Rd, HaiBin Industrisl Zone, QingDao, China 266400

Head Office: B1001 RongAn Center, 700 S. TianTong Rd., NingBo, China, 315100



